ID Tubing Probes

- Part Number Example: **VMBFMF-.720MR-110T**, Flexible, Mag Bias, Ferritic Bobbin, .720” Diameter, Mid Range Frequency (50-500 kHz), 110 Foot Long Shaft, 3/8” Type T Nylon. Typically used for u-bend stainless steel tubing application.
- Part Number Example: **VMBBNF-.830VLF-83PE**, Barnacle scrapper, non magnetic, Ferritic Bobbin, .830” Diameter, Very Low Frequency (5-100 kHz), 83 Foot Long Shaft, 7/16” Polyethylene. Typically used for straight Admiralty Brass tubing application.
- Unique, Titanium Coil Cover for Greater Wear Resistance and Protection

VM	B	X	X	X	-	.XXX	XX	-	.XXX	X

T 5/16 5/16 Type T Nylon
T 3/8 Type T Nylon
H 3/8 Type H Nylon
PE 7/16 Polyethylene

Length of Shaft in Feet

H 100 kHz – 1 MHz
MR 50 – 500 kHz
LF 20 – 200 kHz
VLF 5 – 100 kHz
ULF 1 - 20 kHz

Probe Diameter in Inches

F Ferritic Bobbin – Higher Sensitivity
D Delrin Bobbin

N No Magnet
M Mag Bias
H High Mag Bias

B Barnacle Scrapper
C Chamfered Barnacle Scrapper
F Flexible

Bobbin Probe

VM Products, Inc. 11208 62nd Ave. E., Puyallup, WA 98373 **Tel: (253) 841-2939 Fax: (253) 841-3016**
www.vmproducts.net sales@vmproducts.net